

COMING
FOR YOUR ROAD
TO EXCELLENCE



MOBILE ASPHALT MIXING PLANT



PRODUCT INTRODUCTION



1. Cold Feed System



2. Dust Collector System



3. Dryer & Burning System



4. Bitumen Supply System



5. Mixing System



6. Control Panel

MOBILE ASPHALT MIXING PLANT



PARAMETER TABLE

Model	ZMLB-1000 Mobile Asphalt Mixing Plant	ZMLB-2000 Mobile Asphalt Mixing Plant
Type	Batch Mix / Hot Mix	Batch Mix / Hot Mix
Capacity	80tph *Standard Working Condition	160 TONS PER HOUR (Standard Working Condition, learn more)
Mixer	1000kg/batch	2000kg/batch
Fuel Consumption	Diesel Consumption ≤ 6.5 kg/Ton	Diesel consumption: ≤ 6.5 kg/ton
Weighing Precision	Hot Aggregate $\pm 0.5\%$; Bitumen $\pm 0.3\%$; Filler $\pm 0.2\%$	Hot aggregate: $\pm 0.5\%$; bitumen: $\pm 0.3\%$; filler: $\pm 0.2\%$
Temp. of Finished Asphalt	130°C ~ 160°C	130-160 (adjustable)
Air Emissions	≤ 20 mg/Nm ³	≤ 20 mg/Nm ³
Working Noise	≤ 70 db (A)	≤ 70 db(A)
Operating Mode	Full Auto / Semi Auto / Manual Operation	Full Auto/Semi Auto/Manual Operation
Installed Power	241kW	412kw
Voltage	220V / 380V-50Hz (Ajdustable)	220V/380V-50Hz (adjustable)
Plant Coverage Area	L: 40m, W: 28m, H: 15m	Length: 42m; width: 32m; max height point: 16m
Total Weight	128t	205t

